

BYAF-32 series Weatherproof AC Isolating Switch



Application

BENY The BYAF series of weatherproof isolating switches is a robust range of switches suitable for virtually any external application included in the range are three and four poles switch from 20A to 32A, the base mounted mechanism provides for easier wiring and more wiring room.



Parameter

Designation	BYAF-32	
Pole	3P	4P
Rated Voltage	230~440VAC	230~440VAC
Rated Current	20A	20A
	25A	25A
	32A	32A
Rated Frequency	50Hz	
Rated Insulation Voltage	1000V	
Rated Impulse Withstand Voltage	2.5kV	
Rated Duty	Un-interrupted	
Short Term Withstand Current	750 A For 1Sound	
Short Circuit Making Capacity	750A	
Switch Rating	AC-22A(According to IEC 60947-3)	

Technical Parameter:

- Conform to IEC60947-3
- Rated Current: 20A, 25A, 32A
- Rated Voltage: 230~440VAC
- No. of Pole: 3P, 4P
- EESS Approved

Wiring Diagram

Contacts Wiring Diagram	230~440V	Poles in series	Type Number	IP Rating	Weight / pcs
	20A 25A 32A	Three poles	BYAF-32	IP65	0.50kgs
	20A 25A 32A	Four poles	BYAF-32	IP65	0.54kgs

Dimensions(mm)

